

# TECHNICAL DATA:

NON - PRESSURISED WATER HEATER (5 OR 10 LITRES) FOR ONE OUTLET.



Type	SNU 5	SNU 10	SN 5	SN 10
Colour	White			
Normal capacity	5	10	5	10
Type of system	non-pressurised (open vented)			
To supply one outlet only	Yes	Yes	Yes	Yes

## Dimensions

	mm	421	503	421	503
Height <sup>1</sup>	mm	263	295	263	295
Width	mm	230	275	230	275
Depth	kg	8.1	15	8.1	15
Weight Filled with water	l	10	19	10	19
Volume of mixed water at 40°C <sup>2</sup>	kWh	0.2	0.32	0.2	0.32
Standing heat losses at 65°C/24h					

## Features

Temperature selected up to	°C	85	85	85	85
Element load		2kW	2kW	2kW	2kW
Electrical connection – 1 metre cord & plug		I/N/PE-240V	I/N/PE-240V	I/N/PE-240V	I/N/PE-240V

## Notes:

- 1 With water connection (without fittings)
- 2 The volume of mixed water at 40°C is obtained by adding 15°C cold water to the heater at 65°C

## How to specify:

- Determine if you require a 5 or 10 litre unit.
- Determine which tap is required.
- For a 5 litre unit with kitchen mixer tap, specify model SNU 5 with MES-A or MES-G tapware.

Distributed by:

Free Call: 1800 153 351

• Melbourne • Sydney • Brisbane • Perth • Adelaide • Darwin • Tasmania • New Zealand: 0800 200 510

**STIEBEL ELTRON**

Technik zum Wohlfühlen



WaterMark  
AS 3498 Lic W301  
Standards Australia

www.stiebel.com.au